



Model No.	Part Code	Bearing	Voltage	Frequency	Current	Input Power	Speed	Air Flow	Noise
	No.	○ Sleeve ● Ball	VAC	Hz	A	W	RPM	CFM	dB(A)

Aluminium Housing with Plastic Impeller & Finger Guard



172 x 172 x 55 mm

EC - 27255- S2W- AL	EC065	○	230	50	0.060	6.0	2000	154	40
---------------------	-------	---	-----	----	-------	-----	------	-----	----



220 x 220 x 60 mm

EC - 22060- S2W- AL	EC076	○	230	50	0.070	7.2	1500	257	40
---------------------	-------	---	-----	----	-------	-----	------	-----	----



(S : B :- Sleeve / Ball Bearing) (2 - 230 Volt) (W - Lead Wire) (A - Aluminium Housing) (L - Low Speed)

Plastic Housing with Plastic Impeller & Finger Guard

120 x 120 x 38 mm

EC - 22038- S2W- PL	EC086	○	230	50	0.037	4.1	2650	100	41
---------------------	-------	---	-----	----	-------	-----	------	-----	----



172 x 172 x 55 mm

EC - 27255- S2W- PL	EC067	○	230	50	0.060	6.0	2000	154	40
---------------------	-------	---	-----	----	-------	-----	------	-----	----



220 x 220 x 60 mm

EC - 22060- S2W- PL	EC078	○	230	50	0.070	7.2	1500	257	40
---------------------	-------	---	-----	----	-------	-----	------	-----	----



(S : B :- Sleeve / Ball Bearing) (2 - 230 Volt) (W - Lead Wire) (P - Plastic Housing) (L - Low Speed)

Model No.	Part Code	Air Flow	Bearing	Voltage	Frequency	Current	Input Power	Speed
	No.	← V A →	○ Sleeve ● Ball	VAC	Hz	A	W	RPM

Metal Housing With Aluminium Impeller Ø254 & Finger Guard

325 x 325 x 60 mm

EC - 32560- B0W-MLA	EC091	Throw	●	110~230	50	0.187	24.7	1450
---------------------	-------	-------	---	---------	----	-------	------	------

EC - 32560- B0W-MLV	EC092	Suction	●	110~230	50	0.187	24.7	1450
---------------------	-------	---------	---	---------	----	-------	------	------

(B - Ball Bearing) (0 : - 110-230 Volt) (W - Lead Wire) (M - Metal Housing) (L - Low Speed) (A : V :- Throw / Suction)